Series Delta / DELTA ESD





Technical description

Automatic machine with volumetric dosage.

- o Body in polished steel
- o Moulded side panels polyurethane with stainless steel frame
- o Inbuilt volumetric pump with balanced by-pass
- o Coffee brewing with volumetric dosage (4 doses on each group, continuous brewing button)
- o Self-learning doses programming
- o Hot water delivery with time setting
- o Water mixer
- o Two steam wands in stainless steel with rubber grip and cool touch Teflon insert
- Stainless steel hot water dispenser
- o Porta-filters with Magister OEM handles with cool touch grip
- White LED back-lit six key touch panels with personalized Magister graphics
- o LED indicators
- o LED lights on the working area
- o Electronic boiler temperature control adjustable through the touch pad
- Switching power unit stabilizing voltage fluctuations
- o Electronic pre-infusion (can be disabled through the touch pad)
- o Boiler level control and self-engaging heating element
- O OLED Display with 4 programming buttons. The display shows:
 - machine name;
 - o temperature and water level in the boiler;
 - o coffee brewing timer on each group (chrono-function);
 - o alarms on maintenance;
 - o operational anomalies or failures;
- Through the display buttons it is possible to set:
 - o programmable on/off cycles;
 - o boiler temperature;
 - o pre-infusion time;
 - o alarms on maintenance;
 - o chrono-function;
- o 2 and 3 groups machines in two sizes: standard and "Tall-Cup"

Optional accessories upon request:

- Electronic cup warmer
- Milk warmer/frother temperature-controlled steam wand "EPS"
- Luxury version with mirror-polished side panels and chrome feetLED lighting on the side panels of the machine

Model	DELTA ESD	DELTA ESD
Version	2 GROUPS	3 GROUPS
Dimensions mm.	830x535x500h	1070x535x500h
Boiler capacity	11 lt.	17 lt.
Power	4.500 Watt	5.400 Watt
Voltage	110-220/240V single phase, 230/380/415V threephase	220/240V single phase, 230/380/415V threephase
Weight	68 kg	88 kg